CLINTON COUNTY HEALTH DEPARTMENT

930 A Fairfax St. Carlyle, IL 62231 PH (618) 594-2723 FAX (618) 594-5474 www.clintonco.illinois.gov

PRIVATE SEWAGE DISPOSAL SYSTEM_INFORMATION PACKET

Permit Fee: \$75.00

- 1. All private sewage disposal systems, either new installations, renovations or modifications must have a valid construction permit issued by the Clinton County Health Department.
- 2. General recommended steps to follow for obtaining a valid Private Sewage Disposal Construction Permit:
 - a. Notify the Clinton County Health Department of your private sewage disposal system intentions. The Health Department can provide the homeowner information regarding private sewage systems, types of systems in your area, and soil conditions. On-site consultations may be requested at no charge, with the sanitarian.
 - b. Existing homes or buildings must have all wastewater drains connected to the sewage system (stools, showers, sinks, laundry drains, etc.), excluding perimeter tile, sump pumps and gutter drains. Gray water discharges are prohibited.
 - c. A Soil Evaluation must be completed for all subsurface disposal systems. The majority of soils in Clinton County are unsuitable for subsurface lateral fields. Check Soil Maps before contacting a Certified Professional Soil Classifier for Soil Evaluation.
 - d. Applicants wanting to install a surface discharging private sewage system will have to read and sign the NPDES General Permit Information & Release Form. Sewage Applications for surface discharging systems will not be processed if this form is not signed and submitted with the application. If it has been determined that the effluent from the sewage system may enter Waters of the United States, then the Health Department will issue a Sewage Permit after the applicant obtains an EPA NPDES General Permit.
 - e. Properties located in flood zones may be required to obtain a FEMA LOMA document, for more information contact Clinton County Zoning, 618-594-6655. Properties nearby Carlyle Lake within the flowage easement should contact the Army Corp of Engineers, 618-594-2484, before applying for a sewage permit.
 - f. The Soil Evaluation or NPDES General Permit Information & Release Form and completed Sewage Application with detailed System Design Sketch and \$75.00 permit fee needs to be submitted to the Clinton County Health Department. Upon satisfactory review a Construction Permit will be issued. Allow for 15 days for sewage application processing and review.

Note: If required, obtaining an EPA NPDES permit will delay processing for 30 days.

- g. Contact the Health Department at least 2 days prior to construction for an inspection. An onsite inspection is required for compliance with County Ordinance and State Private Sewage Disposal Act and Code prior to covering.
- 3. Installation of the sewage system must be performed by a State Licensed Private Sewage Disposal Contractor, with the homeowner as an exemption to this regulation. The Health Department has an attached list of licensed sewage contractors working in Clinton County.

- 4. Soil Evaluations are necessary to determine the size of the seepage field and depth to the High Water Table. The bottom of lateral fields cannot be within 2-3 feet of the High Water Table. Attached is a list of Certified Professional Soil Classifiers working in Clinton County.
- 5. Effluent Reduction Trench (ERT) is required on all surface discharging systems. The ERT is based on 150 Square Feet per Bedroom and must be spaced 10 feet apart or greater. NO Soil Evaluation is required for surface discharging systems. The surface discharge point must be at least 25 feet on the owner's property.
- 6. Submitted sewage system design sketch must observe the following minimum allowable distances (FEET).

	Cistern, Well,	Water	Lake, Stream,			
	Suction Line from	Supply	In-ground Pool,	Property	Property	Artificial
	Pump To Well	Line	Other B of W	Dwelling	Line	Drain
Building Sewer	50	10	25	-	-	-
Septic or Aeration Tank	50	10	25	5	5	-
Subsurface Seepage System	75	25	25	10	5	10
Sand Filter	75	25	15	10	5	10
Surface Discharge Effluent Lin	e 50	10	-	-	5	-
Effluent Receiving Trench	75	25	15	10	5	10
Treated Effluent Discharge P	Point 50	10	-	20	25	25

[✓] Aeration unit discharges must be installed so as not to create a nuisance on adjoining properties.

Questions or concerns may be directed to the Clinton County Health Department, Environmental Health, 618-594-2723 ext. 2.

Rev 1/21/2014

[✓] Cleanouts are required every 50 feet from the building to tank.

CLINTON COUNTY

LICENSED PRIVATE SEWAGE DISPOSAL CONTRACTORS

James C. Markus Roger Koerkenmeier Keith Lampe

Aviston, IL 62216 Breese, IL 62230 Germantown, IL 62245 Cell: 444-6683 Cell: 920-8566 Cell: 210-6207

Dennis StrubhartRalph RakersMark SteinkampAviston, IL 62216Carlyle, IL 62231Addieville, IL 62214Office: 228-7702Cell: 581-3975Cell: 246-7623

Tony Lusch Kurt Wuhrle Steve Bost

Salem, IL 62881 Lebanon, IL 62254 Pocahontas, IL 62275 Office: 548-2637 Cell: 741-3849 Cell: 781-8350

Mike Kidd Don Johnson

Vandalia, IL 62471 Richview, IL 62877
Office: 283-1355 Office: 249-8888

SEPTIC TANK MANUFACTURERS & AERATION UNIT DEALERS

Kohnen Concrete Farm Feeds Construction

Germantown, IL 62245 Aviston, IL 62216
Office: 523-4266 Office: 228-7702

LICENSED PRIVATE SEWAGE PUMPERS

A-1 Higgins Septic Service Kramer Septic Service S and S Septic Pumping

Carlyle, IL 62231 Breese, IL 62230 Carlyle, IL 62231

Cell: 973-2719 Office: 526-2561 Office: 749-5057

Professional Soil Classifiers

803 W. State St., O'Fallon, IL 62269 Quality Testing Phone: 618-632-9900 Jerry Berning 2811 Brown St., Alton, IL 62002 Phone: 618-977-7481 **Doug Gaines** 8611 Wiesemann Rd., Worden, IL 62097 Phone: 618-459-8619 Scott Harding 9833 Lower Marine Rd., Marine, IL Phone: 314-581-3553

Please check the Illinois Soil Classifiers Association web page, www.illinoissoils.org/soilconsult.htm to hire a soil classifier for private consulting.

CCHD Permit #	[] New System
	[] Renovation/Replacement

CLINTON COUNTY HEALTH DEPARTMENT

930 A Fairfax St. Carlyle, IL 62231 PH (618) 594-2723 FAX (618) 594-5474

PRIVATE SEWAGE DISPOSAL SYSTEM APPLICATION

Permit Fee: \$75.00

IMPORTANT: Clinton County Health Department does not guarantee trouble free operation of this sewage treatment system by the issuance of a sewage permit or final approval of the installation. The contractor is responsible for the installation in compliance with the Illinois Private Sewage Disposal Licensing Act and Code. By signing this application the property owner assumes full responsibility for maintenance and record keeping, as outlined in Section 905.20(q) of the Illinois Private Sewage Disposal Licensing Act and Code; and assumes full responsibility for any nuisance or health hazard that might result from the use of the system. A designated area for a subsurface seepage system shall be secured prior to and throughout construction of the site.

Homeowner: (current address) Name:				2. <u>Licensed Sewage Contractor</u> : Name				
				A ddmaga	1.			
Address:ZipPhone Number:			Address:Phone Number:					
			License	**************************************				
(Note:	Work not done by hom	eowner mu	st be done by a	State licer	nsed and Clinton	Co. registered con	ntractor)	
Location: Street Address:			Subdivision					
	City:			Z	 Zip:	Lot#		
	Acreage/Lot Size		Pa	rcel #	1			
	Acreage/Lot Size Section	Towr	ship	(N)(S) Range	(E)(V	V)	
	nation: (Check all tha				_			
Residential dwelling # of Bedrooms								
Garbage Disposal Water Softener								
Seasonal dwelling Approximate day Non-Residential # of Employees			oximate days/	year usage	e		- 11	
Water Supp	oly: Public	_ Priva	te	Wel	I Ci	istern (Jther	
	tigation: (Include rep							
Conducted	by:		1 133 77	Date:_		r P .		
Soil Type_			HW	I'		Loading Rate		
Proposed I	Private Sewage Disp ystem discharge to W	osal Syste	e <u>m</u> :	eas (nalva	a liat)		if you be	
vou applied	I for an NPDES perm	aters or th		2 Appl	igation Data:	Dot	, 11 yes 11a	
you applied	HOLAH NEDES PEH	nt with the	COLFA	: Appi	ication Date	F CI	ΠΠι #	
Sentic Tan	k Size	gallons	Manufactuu	er		Π #		
	Seepage Field							
Gravel-less	System		Style/S	sq re. Size	Trenen widt	1		
Buried San	d Filter	sa ft	Style/C Length	ft	Width	ft.		
Other				10.	. , , , , , , , , , , , , , , , , , , ,			
	reatment Unit							
	ne/Model			Treat	tment Capacity	/	GP	
Manufacturer/Dealer								
Location o	Receiving trench/Nuisance lateral installed							

Cistern, Well, Suction Line from Supply In-ground Pool, Property P	Suction Line from Pump To Well 50 50 75	Supply Line 10 10	In-ground Pool, Other B of W 25	Dwelling -			
Pump To Well Line Other B of W Dwelling Line Drain Iding Sewer 50 10 25 Itic or Aeration Tank 50 10 25 5 5 - Surface Seepage System 75 25 25 10 5 10 Id Filter 75 25 15 10 5 10 If Gace Discharge Effluent Line 50 10 5 - Id Filter To 5 25 15 10 5 10 Id Filter To 5 25 15 10 5 10 Id Filter To 5 25 15 10 5 10 Id Filter To 5 25 15 10 5 10 Id Filter To 5 25 15 10 5 10 Id Filter To 5	Pump To Well 50 50 75	Line 10 10	Other B of W 25	Dwelling -			
Iding Sewer 50 10 25	50 50 75	10 10	25	-	Line	Diam	
tic or Aeration Tank 50 10 25 5 5 - surface Seepage System 75 25 10 5 10 6 Filter 75 25 15 10 5 10 6 Filter 75 10 10 10 10 10 10 10 10 10 1	50 75	10				_	
surface Seepage System 75 25 25 10 5 10 d Filter 75 25 15 10 5 10 face Discharge Effluent Line 50 10 - 5 - uent Receiving Trench 75 25 15 10 5 10 ated Effluent Discharge Point 50 10 - 20 25 25 • All wastewater drains MUST be connected to the sewage disposal system (stools, showers, sinks, launder etc.), excluding perimeter tile, sump pumps, gutter drains, etc.	75		23	5	5	_	
d Filter 75 25 15 10 5 10 Face Discharge Effluent Line 50 10 5 - uent Receiving Trench 75 25 15 10 5 10 ated Effluent Discharge Point 50 10 - 20 25 25 • All wastewater drains MUST be connected to the sewage disposal system (stools, showers, sinks, laundretc.), excluding perimeter tile, sump pumps, gutter drains, etc.						10	
Face Discharge Effluent Line 50 10 5 - 5 - 10 uent Receiving Trench 75 25 15 10 5 10 ated Effluent Discharge Point 50 10 - 20 25 25 • All wastewater drains MUST be connected to the sewage disposal system (stools, showers, sinks, laund etc.), excluding perimeter tile, sump pumps, gutter drains, etc.	/ ٦						
 uent Receiving Trench 75 25 15 10 5 10 20 25 25 All wastewater drains MUST be connected to the sewage disposal system (stools, showers, sinks, laund etc.), excluding perimeter tile, sump pumps, gutter drains, etc. 			-	-		-	
 All wastewater drains MUST be connected to the sewage disposal system (stools, showers, sinks, laund etc.), excluding perimeter tile, sump pumps, gutter drains, etc. 			15	10		10	
• All wastewater drains MUST be connected to the sewage disposal system (stools, showers, sinks, laund etc.), excluding perimeter tile, sump pumps, gutter drains, etc.			-				
etc.), excluding perimeter tile, sump pumps, gutter drains, etc.			o the sewage di				e cinke laund
D.4.9. J.Cl., 4.1			_	sposai sys	iem (stoo	is, showers	s, siliks, lauliu
Detailed Sketch	iniciei ine, sump p	oumps, gu	itter trains, etc.				
							S
	he following info	rmation			: T	.111	
Make sure to include the following information in the diagram:		T T. '1'. '		- 11	istances L	abeled	
Make sure to include the following information in the diagram: Water Supply Shown Utilities Shown Distances Labeled Lot Slope (flat, hillside, etc.) Location of Soil Borings Bodies of Water						· · · · · · · · · · · · · · · · · · ·	
	i	75 nt 50 ins MUST be conmeter tile, sump p	75 25 nt 50 10 ins MUST be connected to meter tile, sump pumps, gu	75 25 15 nt 50 10 - ins MUST be connected to the sewage dismeter tile, sump pumps, gutter drains, etc.	75 25 15 10 Int 50 10 - 20 Ins MUST be connected to the sewage disposal sysmeter tile, sump pumps, gutter drains, etc.	75 25 15 10 5 nt 50 10 - 20 25 ins MUST be connected to the sewage disposal system (stoo meter tile, sump pumps, gutter drains, etc.	75 25 15 10 5 10 nt 50 10 - 20 25 25 ins MUST be connected to the sewage disposal system (stools, showers meter tile, sump pumps, gutter drains, etc.

Date

Revised 1/14

Signature of Contractor

(Office Use) Date fee paid_____ Check #___

NPDES General Permit Information and Release Form

The United States Environmental Protection Agency has made a final decision to issue the National Pollutant Discharge Elimination System (NPDES) General Permit for point source discharges of pollutants from new or replacement individual wastewater treatment systems to federally protected waters in Illinois. This General Permit will become effective on February 10, 2014.

According to the EPA, it is the responsibility of the potential discharger to determine whether or not his or her system might discharge to a water of the United States. EPA suggests a common sense way of evaluating whether you are required to be covered by a NPDES General Permit, if you were to install a new or replacement surface discharging system on your land, would effluent or pollutants from your system end up in a water of the United States or a conveyance to a water of the United States. The NPDES General Permit defines Waters of the United States as follows:

Waters of the United States- EPA's regulation at 40 C.F.R § 122.2 defines Waters of the United States as follows:

- 1. All waters which are currently used, were used in the past, or may be susceptible to use in interstate or foreign commerce, including all waters which are subject to the ebb and flow of the tide;
- 2. All interstate waters, including interstate "wetlands;"
- 3. All other waters such as intrastate lakes, rivers, streams (including intermittent streams), mudflats, sandflats, "wetlands," sloughs, prairie potholes, wet meadows, playa lakes, or natural ponds, the use, degradation, or destruction of which would affect or could affect interstate or foreign commerce including any such waters:
 - a. Which are or could be used by interstate or foreign travelers for recreational or other purposes;
 - b. From which fish or shellfish are or could be taken and sold in interstate or foreign commerce; or
 - c. Which are used or could be used for industrial purposes by industries in interstate commerce:
- 4. All impoundments of waters otherwise defined as waters of the United States under this definition;
- 5. Tributaries of waters identified in paragraphs 1 through 4 of this definition;
- 6. The territorial sea: and
- 7. "Wetlands" adjacent to waters (other than waters that are themselves wetlands) identified in paragraphs 1 through 6 of this definition.

If you have determined that discharge from your private sewage system may enter Waters of the United States or conveyances to Waters of the United States, then you will need to apply for an NPDES General Permit or install an alternative subsurface sewage treatment system. The Clinton County Health Department recommends installing a subsurface system.

To obtain coverage under the NPDES General Permit:

- The property owner must submit a notice of intent (NOI) and the <u>supplemental information</u> required in the General Permit.
 - Technological Feasibility: Owners or operators must submit a written determination that concludes that an individual or Soil Based Cluster System and all other alternatives to a Surface Discharging system are not technologically feasible. Feasibility determinations for soil based systems shall be based on Soil Investigation and Site Evaluation Reports. Note, alternatives to surface discharging systems are not limited to a septic tank followed by effluent reduction trench.
 - Economic Feasibility: EPA has developed a spreadsheet tool that must be used by the applicant to calculate average annualized costs and determine whether or not they exceed 2% of their annual household adjusted gross income, as averaged over the three most recent full calendar years.
- Send the NOI via certified mail to USEPA, Region 5, Water Division, Chicago.
- EPA will review the NOI and make a decision 30 calendar days from the date it receives the NOI.
- Unless coverage is denied, the property owner is eligible to discharge in accordance with the General Permit **30 calendar days** after EPA receives the NOI.

If coverage under the NPDES General Permit is denied, EPA will notify both the applicant and the applicable county health department of EPA's decision to deny permit coverage. EPA will notify both parties by telephone and follow up with a formal letter on the decision.

It is important to inform you that if you do obtain an NPDES General Permit, you will be required to comply with inspections, monitoring, effluent sampling every 6 months, reporting, records retention, and other tasks described in the permit.

For more information concerning NPDES General Permit go to the USEPA website at www.epa.gov/region5/water/npdestek/surfacedischarge/ or contact Mark Ackerman with the USEPA, 312-353-4145, ackerman.mark@epa.gov, or contact Holly Timmermann with the Clinton County Health Department, 618-594-2723, ext. 2, holly.timmermann@clintonco.illinois.gov.

Applicants for a Clinton County Sewage Permit with an existing or proposed private sewage system that may discharge to Waters of the United States must sign and date below to certify that you fully understand the contents of this document and the requirements of the NPDES General Permit, and accept full responsibility for violations of the NPDES permit and nuisances or environmental health hazards that may result from the use of your system.

hazards that may result from the use of your system.	int and nuisances of environmental
Signature of Property Owner	Date

SEPTIC SYSTEM DO'S AND DON'TS

DO's

- Learn the location of your septic tank and lateral field. Keep a sketch of it handy along with your maintenance records for service visits.
- Have your septic system inspected annually
- Have your septic tank pumped out regularly by a Licensed Private Sewage Pumper.
- Know the location of your septic tank inspection port. The inspection port should be within 12 inches of the ground surface.
- Call a professional whenever you experience problems with your system, or if there are any signs of system failure
- Keep a detailed record of repairs, pumpings, inspections, permits issued, and other maintenance activities.
- Conserve water to avoid overloading the system. Be sure to repair any leaking faucets or toilets. Spread laundry out over the week. Once a week multiple loads are not recommended.
- Divert other sources of water, like roof drains, house footing drains and sump pumps, away from the septic system. Excessive water can overload the drain field.

DON'Ts

- Go down into a septic tank. Toxic gases are produced by the natural treatment processes in septic tanks and can kill in minutes. Extreme care should be taken when inspecting a septic tank, even when just looking in.
- Allow anyone to drive or park over any part of the septic system.
- Plant anything over or near the drain field except grass. Roots from trees or shrubs may clog and damage the drain lines.
- Dig in your drain field or build anything over it, and don't cover the drain field with a hard surface such as concrete or asphalt. The area over the drain field should have only a grass cover. The grass will prevent erosion and will help remove water.
- Make or allow repairs to your septic system without obtaining the required Health Department Permit. Use Licensed Private Sewage Disposal Contractors when needed.
- Use septic tank additives. These products usually do not help and some may even be harmful to your system.
- Use your toilet as a trash can or poison your septic tank and ground water by pouring harmful chemicals or cleansers down the drain. Harsh chemicals can kill the beneficial bacteria that treat your waste water.
- Use a garbage disposal without checking with your local Health Department to make sure your septic tank can accommodate the additional waste.
- Allow backwash from home water softeners or hot tub to enter the septic tank.

DO NOT FLUSH:

- > Coffee grounds
- > Personal Medicines
- > Disposable diapers
- **≻** Kitty litter
- > Sanitary napkins
- > Tampons
- Cigarette butts
- **Condoms**
- > Fats, Grease or Oil
- > Paper towels
- > Hazardous chemicals
 - o These items can destroy the biological digestion taking place within your septic tank.

MAINTENANCE OF AERATION UNITS

OWNER RESPONSIBILITIES:

READ THE OWNER'S MANUAL, if you do not receive a manual please contact the installer, dealer or manufacturer.

- ✓ The aeration unit is not maintenance free and at some time may need to be pumped. The aeration unit should not emit any septic odors.
- ✓ On a monthly basis you should check for odors around the aeration unit and in the water being discharged. Report any odors and any discolored water (effluent) being discharged.
- ✓ Discharged effluent must be chlorinated, maintain chlorine feeder and chlorine tank as needed.
- ✓ Aerobic treatment units require evaluation and maintenance at least once every 6 months.

TO ENSURE PROPER OPERATION AND MINIMIZE PROBLEMS, PLEASE REVIEW AND FOLLOW THESE GUIDELINES:

- 1. DO NOT add strong detergents, disinfectants or bleach (other than very small amounts used in daily household cleaning and laundry) to the system.
- 2. DO NOT allow the discharge of any clear water discharges (water softeners, air conditioners, footing drains, sump pumps, etc.) into the system.
- 3. DO NOT allow any disposable items such as: diapers, tampons, sanitary napkins, large quantities of paper products, tobacco products, non-biodegradable items, into the system.
- 4. DO NOT allow coffee grounds, chemical waste, paint, personal medicines, oils or grease (such as cooking grease) into the system.
- 5. Anything you cannot eat or digest should not be placed in your aeration unit.